


Light Up Orbit / Earth Always In

Spec Guide

Light Up Orbit

Available for order from second quarter



Materials
Stainless steel body
Plastic casing

Installation
Floor/ground/wall/ceiling*


Operating temperature
From -30°C to +45°C

*except for ø 80 mm

Colour temperature - CRI
4000K - CRI 80
3000K - CRI 90

IP Rating
IP68 protection on the product and IP68 connectors.
(the product is not suitable for use in swimming pools and fountains).

LED duration
50.000 h L80 B10 - Ta 40° C.



Temperature <40°C




Static load resistance
2000 Kg

Fixed Optic

Diameter Ø	28	50	80
Optics			
	12°-30°	10°-20°-40°	10°-20°-40°
	Diffuser 90°	Diffuser 90°	Diffuser 90°
		Light Blade	Light Blade
Product height	68 mm	74 mm	83 mm
Luminous flow (Lm)	100	200-300	500
W	1	2-3	7
Control	350mA max	350/700mA max	500mA max

Washer Optic

Diameter Ø	28	50	80
Optics			
		Floor Washer	Floor Washer
		74 mm	83 mm
Product height		74 mm	83 mm
Luminous flow (Lm)		250	500
W		2	5
Control		350mA max	500mA max



Materials

Stainless steel body
Plastic casing

Installation

Floor/ground

Operating temperature

From -30°C to +45°C

Colour temperature - CRI

4000K - CRI 80


3000K - CRI 90

IP Rating

IP68 protection on the product and IP68 connectors.
(the product is not suitable for use in swimming pools and fountains).

LED duration

50.000 h L80 B10 - Ta 40° C.



Temperature <40°C



Static load resistance
5000 Kg

Fixed Optic

Diameter Ø	144	200	250
Optics			
	10°-16°-30°-50°	8°-12°-18°-28°-42°	5°-12°-16°-30°-48°
			
	Diffuser 90°	Diffuser 90°	Diffuser 90°
			
	Light Blade		
Product height	175 mm	179 mm	201 mm
Luminous flow (Lm)	500-1000	800-1900-2200	1000-2500-3000
W	5-7	8,5-15-15,3	10-17,2-19,4
Control	On/Off	DALI	DALI

Adjustable Optic patent pending

Diameter Ø	144	200	250
Optics			
	10°	8°-12°-25°-40°	5°-12°-25°-40°
Product height	147 mm	166 mm	194 mm
Luminous flow (Lm)	1000	800-2000	800-2800
W	7	8-15	8-22
Control	On/Off	DALI	DALI

0-30°



358°



Washer Optic

Diameter Ø	144	200	250
Optics			
	Wall Washer	Wall Washer	Wall Washer
Product height	175 mm	179 mm	201 mm
Luminous flow (Lm)	1200	1800	2400
W	12	18	24
Control	On/Off	DALI	DALI

Overview

Light Up Orbit
Fixed Optic

Ø28



Ø50



Ø80



Optics



Spot α 12°



Flood α 30°



Diffuser α 90°



Spot α 10°



Medium α 20°



Wide Flood α 40°



Diffuser α 90°



Light Blade



Spot α 10°



Medium α 20°



Wide Flood α 40°



Diffuser α 90°



Light Blade

Accessories



Plastic outer case for floor installation



Plastic casing for wall/ceiling-mounted installation

Light Up Orbit
Washer Optic

Ø50



Ø80



Optics



Floor Washer



Floor Washer

Accessories



Plastic outer case for floor installation



Plastic casing for wall/ceiling-mounted installation

Light Up Earth
Washer Optic

Ø144



Ø200



Ø250



Wall Washer



Wall Washer



Wall Washer



Accessories



Plastic outer case for floor installation

Ø144



Ø200



Ø250



Optics

—



Spot α 10°



Medium α 16°



Flood α 30°



Wide Flood α 50°




Diffuser α 90°



Light Blade



Super Spot α 8°



Spot α 12°



Medium α 18°



Flood α 28°



Wide Flood α 42°




Diffuser α 90°

—



Super Spot α 5°



Spot α 12°



Medium α 16°



Flood α 30°



Wide Flood α 48°



Diffuser α 90°

—

Accessories



Refractor for elliptical distribution



Diffusing glass



Honeycomb Louvre



Plastic outer case for floor installation

Ø144



Ø200



Ø250




Optics



Spot α 10°




Super Spot α 8°




Spot α 12°



Medium α 25°



Super Spot α 5°



Spot α 12°



Medium α 25°



Wide Flood α 40°



Wide Flood α 40°

Accessories



Plastic outer case for floor installation

